



FA53401756 Matte Stainless Steel

### A-Rise 145 High Emission NEW


Designed by FLOS Outdoor



LED light source included. Integrated 24V dc ON/OFF remote electric power supply. Adjustment on vertical axis: 15° max. Rotation on horizontal axis: 359° max. Remote power supply that must be placed in a junction box, equipped with a protruding, 400 mm cable with an M12 screw-on connector that guarantees the water tightness of the luminaire, and with a 250 mm cable for the connection to the power line. Extra clear transparent glass. Adjustable light intensity version available upon request.

Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 



### Main specifications

Mounting	Ground recessed
Enviroment	Outdoor wet location
LED type	LED array
Number of heads	1
Power (W)	6
System power (W)	9
Source flux (lm)	959
System flux (lm)	610

### Physical

Colour	Matte Stainless Steel
Orientation	Adjustable
Rotation (°)	359
Longitudinal tilting (°)	15
IP internal	66/67

### Download

Mounting instructions

<u>↓</u> ZIP

### Photometric Files

LDT / IES

₹ ZIP

### **Technical Drawings**

2D	$\overline{\mathbf{A}}$	ZIP
3D	<u></u>	ZIP











https://professional.flos.com/en/global/product/a-rise-145-high-emission-fa53401756/

FA53401756

### Schematic light drawing



Beam	Angle:	54°
h(m)	E(lx)	D(m)
1	969	1.01
2	242	2.03
3	108	3.04
4	61	4.05
5	39	5.06

### Electrical

Insulation class	II
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Driver	Remote included
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

## **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

# Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	50
Beam angle C90-270 (°)	50

#### **Notes**

Dimmable version on request

### **Accessories & Power Supply**



### REQUIRED Accessory

F4597000

Box for installation



#### OPTIONAL Accessory

F990C00A000


2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)



#### OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



### OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)