



FA51801656 Matte Stainless Steel

A-Rise 65 Hp Ceiling NEW


Designed by FLOS Outdoor



LED source included. 24V dc remote electric power supply to be ordered separately. Includes a spring for plasterboard installations. The luminaire is equipped with a protruding, neoprene, 200 mm cable and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Transparent polycarbonate diffuser. Adjustable light intensity version available upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Enviroment	Outdoor wet location
LED type	Power LED
Number of heads	1
Power (W)	3.3
System power (W)	4.5
Source flux (lm)	359
System flux (lm)	267

Physical

Colour	Matte Stainless Steel
Orientation	Fixed
IP internal	66
IP external	66

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D	$\underline{\bot}$	ZIP
3D	$\overline{\mathbf{A}}$	ZIP









ΙK

IΡ

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Non-replaceable light source

https://professional.flos.com/en/global/product/a-rise-65-hp-ceiling-fa51801656/

FA51801656

Schematic light drawing



Beam Angle:		13°
h(m)	E(lx)	D(m)
1	3278	0.22
2	820	0.44
3	364	0.67
4	205	0.89
5	131	1.11

Luminous flux luminaire 267 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12

Electrical

Insulation class	III
Main voltage (Vac)	24
Driver	Remote excluded
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Notes

Dimmable version on request

Accessories & Power Supply



OPTIONAL Accessory

F990C050000

2 way terminal block 2 poles IP68 H2O stop. (Ø4÷6,9mm cable)



OPTIONAL Power supply

F990B23AZ00

Power supply 24Vdc 35W /120-270V IP67 Class II selv.



OPTIONAL Power supply

RF25754

'Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP20 Class II selv._Non Dimmable



OPTIONAL Power supply

RF2575

Power supply 24V 10W / 110-240V IP67 Class II selv._Non Dimmable



OPTIONAL Power supply

RF25749

Power supply 24Vdc 70W / 220-240V IP67 Class II selv. Non Dimmable



OPTIONAL Power supply

RE2575

Power supply 24Vdc 50W / 120-240V IP67 Class II selv. Non Dimmable



OPTIONAL Power supply

RF25747

Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable



OPTIONAL Power supply

RF25748

Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP65 Class II selv. Non Dimmable