

## Accent Lighting 3000K. Set of 12 spots for circle of light. Non Dimmable



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| System power (W)       | 54                  |
| Source flux (lm)       | 3780                |
| System flux (lm)       | 2417                |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | Black |
| Trim                | No    |
| Recessed depth (mm) | 150   |
| Net weight (kg)     | 3.37  |
| IP internal         | 20    |

### Download

Mounting instructions  PDF


### Photometric Files

LDT / IES  LDT

### Ecodesign and Energy Labelling




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



Schematic light drawing



Photometric

|                       |           |
|-----------------------|-----------|
| Light distribution    | Symmetric |
| CCT (K)               | 3000      |
| Beam angle C0-180 (°) | 12        |
| Extreme cut off       | Yes       |
| UGR <sub>L</sub>      | <10       |

Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | II           |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| LED current (mA)   | 1050         |
| Dimmable           | Yes          |
| Dimming interface  | Not Dimmable |

Notes

Junction box, power supply and cables included.