



Aim Small

■ F0095009 - White

Designed by Ronan & Erwan Bouroullec

Suspended light fitting. Body in varnished aluminium sheet, shade in photo-etched optical polycarbonate. Internal reflector in photo-etched PC. Directionable body. Powered directly from mains. The LED can be dimmed with a «Triac for Led» dimmer approved by Flos. Flos does not respond in case of wrong electrical connection system installations. The cable has a useful length of 9 metres and thus the lamp can be suspended 3 metres from the ceiling. Multiple rose with capacity to connect up to 5 Aim Small also available.

Main specifications

Mounting	Suspension	Lamp holder	LED Module
Environment	Indoor dry location	Autoprotected Lamp	No
Light source type	LED	Number of heads	1
Light source replaceable	Replaceable (LED only) light source by a professional LED Module	Source Power (W)	12
		System Flux (lm)	725




LED type


LED type

Lighting Type
Lighting distribution
CCT (K)
CRI>
Cold Beam Lighting
Extreme Cut off

Direct
Roto symmetric
2700
90
No
No



Luminous flux luminaire
725 lm



Optical

Insulation class	II	Batteries Inside	No
Frequency (Hz)	50/60	Cord length (mm)	9000/3000
Main Voltage (Vac)	220-240	Charging Min Time	No
Driver	Integrated		
Dimmable type	Mains Cut Dimming		

Electrical

Colour	White
Net weight (kg)	1.35
Gross weight (kg)	2.98
IP	20
IP external	20

Physical



Aim Small



Aim Dimmer
RF22227

Aim Canopy
F0093009