



FA51308012 Forest Green

Aimer 2 NEW


Designed by FLOS Outdoor, 2011



LED source included. Remote electrical power supply 24V dc ON/OFF to be ordered separately. Equipped with a 2000 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Fixing bracket included. Extraclear transparent glass. The metal nail for ground installation needs to be ordered separately. Dimmable version available upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793632667
Mounting	Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	2
System power (W)	3.4
Source flux (lm)	199
Lumen Output (lm)	138

Physical

Colour	ur Forest Green	
Orientation	Directional	
Longitudinal tilting (°)	182	
Net weight (kg)	0.34	
Package height (mm)	80	
Package width (mm)	130	
Package length (mm)	130	
IP internal	65	

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D	$\underline{\boldsymbol{\gamma}}$	ZIP
3D	$\overline{\mathbf{A}}$	ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F













https://professional.flos.com/en/global/product/aimer-2-fa51308012/

FA51308012

Schematic light drawing



Bear	Beam Angle:	
h(m)	E(lx)	D(m)
1	1971	0.21
2	493	0.43
3	219	0.64
4	123	0.86
5	79	1.07

Luminous flux luminaire 138 lm

Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Notes

Dimmable version on request

Accessories & Power Supply



OPTIONAL Power supply

RF25754

'Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP20 Class II selv._Non Dimmable



OPTIONAL Power supply

RF25752

Power supply 24Vdc 20W / 220-240V IP67 Class II selv. Non Dimmable



OPTIONAL Power supply

RF25757

Power supply 24V 10W / 110-240V IP67 Class II selv._Non Dimmable



OPTIONAL Power supply

RF25748

Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP65 Class II selv. Non Dimmable



OPTIONAL Power supply

F990B27A000

Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable



OPTIONAL Power supply

E990R28A000

Power supply 24Vdc 50W / 220-240V IP67 Class I selv. Non Dimmable



OPTIONAL Power supply

RF25747

Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable



OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2