



Aimer 2 NEW

Designed by FLOS Outdoor, 2011




LED source included. Remote electrical power supply 24V dc ON/OFF to be ordered separately. Equipped with a 2000 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Fixing bracket included. Extraclear transparent glass. The metal nail for ground installation needs to be ordered separately. Dimmable version available upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Anthracite



Main specifications

| EAN | 8054793632759 |
|------------------------|----------------------|
| Mounting | Ground |
| Environments | Outdoor wet location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| Power (W) | 2 |
| System power (W) | 3.4 |
| Source flux (lm) | 199 |
| Lumen Output (lm) | 138 |

Physical

| | 7 ti te il delec |
|--------------------------|------------------|
| Orientation | Directional |
| Longitudinal tilting (°) | 182 |
| Net weight (kg) | 0.34 |
| Package height (mm) | 80 |
| Package width (mm) | 130 |
| Package length (mm) | 130 |
| IP internal | 65 |

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

| 2D | $\overline{\mathbf{A}}$ | ZIP |
|----|-------------------------|-----|
| 3D | <u></u> | ZIP |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F











https://professional.flos.com/en/global/product/aimer-2-fa51308033/

FA51308033

Schematic light drawing



| Bear | Beam Angle: | |
|------|-------------|------|
| h(m) | E(lx) | D(m) |
| 1 | 1971 | 0.21 |
| 2 | 493 | 0.43 |
| 3 | 219 | 0.64 |
| 4 | 123 | 0.86 |
| 5 | 79 | 1.07 |

Luminous flux luminaire 138 lm

Photometric

| Light distribution | Symmetric |
|------------------------|-----------|
| CCT (K) | 2700 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 12 |
| Beam angle C90-270 (°) | 12 |
| Extreme cut off | No |

Electrical

| Insulation class | III |
|--------------------|-----------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 24 |
| Power supply | Remote excluded |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Dimming interface | Not Dimmable |
| Emergency | No |

Notes

Dimmable version on request

Accessories & Power Supply









OPTIONAL Power supply

RF25752

Power supply 24Vdc 20W / 220-240V IP67 Class II selv. Non Dimmable

OPTIONAL Power supply

RF25757

Power supply 24V 10W / 110-240V IP67 Class II selv._Non Dimmable

OPTIONAL Power supply

RF25748

Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP65 Class II selv. Non Dimmable

OPTIONAL Power supply

F990B27A00

Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable



OPTIONAL Power supply

RF25747

Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable



OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2



OPTIONAL Power supply

F990R28A000

Power supply 24Vdc 50W / 220-240V IP67 Class I selv. Non Dimmable