


## Aimer 3 Constant Current NEW

Designed by FLOS Outdoor, 2011



LED source included. Remote power supply 350/500 mA ON/OFF and dimmable 1-10V or DALI. Must be ordered separately. Serial connection. Equipped with a 2000 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Extraclear transparent glass. The metal nail for ground installation needs to be ordered separately.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8054793606965
Mounting	Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	5
System power (W)	5.1
Source flux (lm)	431
Lumen Output (lm)	364

### Physical

Colour	Anodized Aluminium
Orientation	Directional
Longitudinal tilting (°)	185
Net weight (kg)	0.65
Package height (mm)	75
Package width (mm)	145
Package length (mm)	235
IP internal	67
IP external	66

### Photometric Files

LDT / IES	<a href="#">ZIP</a>
LDT / IES	<a href="#">ZIP</a>

### Technical Drawings


2D	<a href="#">ZIP</a>
3D	<a href="#">ZIP</a>

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	30
Beam angle C90-270 (°)	30
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency	No

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL  
Accessory

F990C00A000  
2 way terminal block 4 poles IP68  
H20 stop. (ø5,5÷12mm cable)



OPTIONAL  
Accessory

FA136  
Ground Spike Aimer 1/Aimer  
2/Aimer 3/Perseo 2



OPTIONAL  
Power supply

FA129  
Power supply 16 x 1W/  
110÷240V - Iout 350mA  
(12x1W@110V) IP20 Class II Selv  
Eq. Dimmable Push-Dimm Or  
1.10V



OPTIONAL  
Power supply

FA184  
Power supply 16 x 1W/  
110÷240V - Iout 350mA  
(12x1W@110V) IP67 Class II Selv  
Dimmable Push-Dimm Or 1.10V



OPTIONAL  
Power supply

FA135  
Power supply 13 x 2W/  
110÷240V - Iout 500mA  
(7x2W@110V) IP20 Class II Selv.  
Eq. Dimmable Push-Dimm Or  
1.10V



OPTIONAL  
Accessory

FA5130  
Visor for Aimer 3



OPTIONAL  
Power supply

FA68  
Power supply 10 x 1W/  
100÷265V - Iout 350mA  
(7x1W/110V) IP40 Class II Selv  
Eq.



OPTIONAL  
Power supply

FA218  
Power supply 13 x 2W/  
110÷240V - Iout 500mA  
(7x2W@110V) IP67 Class II Selv.  
Dimmable Push-Dimm Or 1.10V



OPTIONAL  
Power supply

RF25754

'Power supply dual function Vout  
24Vdc: 8W/100÷240V Iout  
350ma: 6x1W/100÷240V IP20  
Class II selv.\_Non Dimmable



OPTIONAL  
Power supply

RF25748

Power supply dual function Vout  
24Vdc: 8W/100÷240V Iout  
350ma: 6x1W/100÷240V IP65  
Class II selv. Non Dimmable