

Almendra Linear Suspension 3


Designed by Patricia Urquiola, 2022

48W - 1755lm - 2700K - CRI> 95

Suspension lamp with diffused light emission available in linear and organic compositions. Tubular structure made of aluminium and CNC aluminium terminals with matte or metallized finish. Edge Lighting technology integrated. Light units can be turned by steps of 60° within the structure in order to change the direction of the light emitted. Metal rosette with matte white finish. The integrated electronics in the ceiling rose allow the use of different dimming systems: 1-10V, DALI, push-dim or potentiometer. Useful length of the cable 3 mt. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Edge Lighting
Power (W)	48
System flux (lm)	1755

Physical

Color	Off-white
Length (in)	50.63
Cord color	Clear
Cord length (in)	110.236
Canopy color	White
Canopy length/diameter (in)	16.535
Canopy width (in)	3.937
Canopy height (in)	1.732
Net weight (lb)	15.74
Package volume (in)	9051.69
IP internal	20

Download

Mounting instructions



Photometric Files

LDT / IES





IP
20

Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	95

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional


Spare Parts



04.	Terminal Joint L90 Almendra White	RF32773
05.	Assembly Almendra Suspension Wiring & Connections White	RF32530
06.	Assembly Almendra Suspension Central Feed White	RF32521
08.	Assembly Almendra Suspension Body White	RF32514
09.	Kit with screws and allen key	RF3160100



RF32773
Terminal Joint L90 Almendra
White



RF32530
Assembly Almendra Suspension
Wiring & Connections White



RF32521
Assembly Almendra Suspension
Central Feed White



RF32514
Assembly Almendra Suspension
Body White



RF3160100
Kit with screws and allen key