



Almendra Organic Suspension Short 2 Primer

Designed by Patricia Urquiola, 2022



31W - 1170lm - 2700K - CRI> 95

Suspension lamp with diffused light emission available in linear and organic compositions. Tubular structure made of aluminium and CNC aluminium terminals with matte or metallized finish. Edge Lighting technology integrated. Light units can be turned by steps of 60° within the structure in order to change the direction of the light emitted. Metal rosette with primer finish. The integrated electronics in the ceiling rose allow the use of different dimming systems: 1-10V, DALI, push-dim or potentiometer. Useful length of the cable 3 mt. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607050989
Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Edge Lighting
Power (W)	31
Lumen Output (lm)	1170

Physical

Colour	Off-white
Length (mm)	1326
Cord colour	Clear
Cord length (mm)	2600
Canopy colour	Primer
Canopy length/diameter (mm)	799
Canopy width (mm)	70
Canopy height (mm)	39
Net weight (kg)	8.17
Package volume (m3)	0.21
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files


LDT / IES [↓ LDT](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	95

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Spare Parts




01.	Driver 96W 48V 220-240V	RF32405
02.	Led dimmer kit	RF34197
03.	Almendra S Y primer cover	RF0429100
04.	Kit with screws and allen key	RF3160100
05.	Assembly Almendra Suspension Body White	RF32514
06.	Almendra S Arc/Y terminal joint L31 White	RF33246



RF32405
Driver 96W 48V 220-240V



RF34197
Led dimmer kit



RF0429100
Almendra S Y primer cover



RF3160100
Kit with screws and allen key



RF32514
Assembly Almendra Suspension
Body White



RF33246
Almendra S Arc/Y terminal joint
L31 White