




Almendra Organic Suspension Short 2 Primer

Designed by Patricia Urquiola, 2022




32W - 914lm - 2700K - CRI> 95

Suspension lamp with diffused light emission available in linear and organic compositions. Tubular structure made of aluminium and CNC aluminium terminals with matte or metallized finish. Edge Lighting technology integrated. Light units can be turned by steps of 60° within the structure in order to change the direction of the light emitted. Metal rosette with primer finish. The integrated electronics in the ceiling rose allow the use of different dimming systems: 1-10V, DALI, push-dim or potentiometer. Useful length of the cable 3 mt. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607051535
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Edge Lighting
Power (W)	32
System flux (lm)	914

Physical

Color	Nude
Length (in)	52.21
Cord color	Clear
Cord length (in)	102.362
Canopy color	Primer
Canopy lenght/diameter (in)	31.457
Canopy width (in)	3.937
Canopy height (in)	1.732
Net weight (lb)	18.01
Package volume (in)	12934.46
IP internal	20

Download Mounting instructions	⊥ PDF
Photometric Files LDT/IES	⊥ LDT

https://professional.flos.com/en-US/us/product/almendra-organic-suspension-short-2-primer-fu039626/

FU039626







Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	95

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120
Driver	Integrated
Dimmable	Yes
Dimmable Dimming type	Yes Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **E**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



O4. Kit with screws and allen key RF3160100
 O5. Assembly Almendra Suspension RF32516
 Body Nude

 O6. Almendra S Arc/Y terminal joint RF33247
 L31 Brown



FLOS

RF3160100

Kit with screws and allen key

RF32516
Assembly Almendra Suspension
Body Nude

RF33247

Almendra S Arc/Y terminal joint L31 Brown