



Almendra Organic Suspension Short 3 Primer

Designed by Patricia Urquiola, 2022

45W - 1338lm - 2700K - CRI> 95

Suspension lamp with diffused light emission available in linear and organic compositions. Tubular structure made of aluminium and CNC aluminium terminals with matte or metallized finish. Edge Lighting technology integrated. Light units can be turned by steps of 60° within the structure in order to change the direction of the light emitted. Metal rosette with primer finish. The integrated electronics in the ceiling rose allow the use of different dimming systems: 1-10V, DALI, push-dim or potentiometer. Useful length of the cable 3 mt. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8059607051146
Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Edge Lighting
Power (W)	45
Lumen Output (lm)	1338

Physical

Colour	Bay Blue Metallized
Length (mm)	1611
Cord colour	Clear
Cord length (mm)	2600
Canopy colour	Primer
Canopy length/diameter (mm)	799
Canopy width (mm)	70
Canopy height (mm)	39
Net weight (kg)	9.83
Package volume (m3)	0.25
IP internal	20

Download

Mounting instructions  PDF

Photometric Files


LDT / IES  LDT

Technical Drawings


2D  ZIP

3D  ZIP

 Bim  ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	95

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E


Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Spare Parts



00.	Almendra S Y primer cover	RF0429100
00.	Kit with screws and allen key	RF3160100
00.	Driver 96W 48V 220-240V	RF32405
00.	Assembly Almendra Suspension	RF32518
	Body Bay Blue Metallized	
00.	Almendra S Arc/Y terminal joint	RF33250
	L31 Met. Green	
00.	Led dimmer kit	RF34197



RF0429100

Almendra S Y primer cover



RF3160100

Kit with screws and allen key



RF32405

Driver 96W 48V 220-240V



RF32518

Assembly Almendra Suspension
Body Bay Blue Metallized



RF33250

Almendra S Arc/Y terminal joint
L31 Met. Green



RF34197

Led dimmer kit