

FLOS

■ F0413030 Black


Arrangements Drop Down

Designed by Michael Anastassiades, 2018



30W - 1530lm - 2700K

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone. Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up. Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings. The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607014158
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	30
System flux (lm)	1530

Physical

Colour	Black
Length (mm)	495
Cord length (mm)	2500
Net weight (kg)	0.65
Package height (mm)	45
Package width (mm)	545
Package length (mm)	755
Package volume (m3)	0.02
IP internal	20

Download

[Mounting instructions](#)  PDF

[Spare Parts](#)  PDF

Photometric Files

[LDT / IES](#)  LDT

Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP


[Bim](#)  ZIP



IP
20


Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional

Schematic light drawing



Luminous flux luminaire
1530 lm


Photometric

Light distribution	Symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	48
LED voltage Vf (Vdc)	null
Driver	Remote
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No


Accessories & Power Supply



REQUIRED

F0415030

Arrangements Big Rose



REQUIRED

F0416030

Arrangements Small Rose



REQUIRED

F0418030

Arrangements Recessed Rose