



05.5160.ES.CB Brushed Bronze

Atom 200 Casambi Dimmable NEW



Designed by FLOS Architectural, 2023




10.5W - 395lm - 2700K - CRI> 90 - Beam^o 110

LED general lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	10.5
Source flux (lm)	1005
System flux (lm)	395

Physical

Color	Brushed Bronze
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
IP internal	20



Family spec sheet	<u>↓</u> ZIF
Mounting instructions	⊥ PDF

Photometric Files

LDT / IES



Technical Drawings

2D	₹ ZIP
3D	₹ ZIP

















https://professional.flos.com/en-US/us/product/atom-200-casambi-dimmable-05.5160.es.cb/

05.5160.ES.CB

Schematic light drawing



Beam	Angle:	110°
h(m)	E(lx)	D(m)
1	145	2.86
2	36	5.73
3	16	8.59
4	9	11.45
5	6	14.32

30°	145 cc	1	30°	
Lumino	us flux	lumi	naire	

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Non-replaceable light source

Photometric

Extreme cut off	No
Beam angle C90-270 (°)	110
Beam angle C0-180 (°)	110
McAdam steps (SDCM)	2
CRI>	90
CCT (K)	2700
Light distribution	Symmetric
Lighting type	Direct

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	420
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable Casambi
Dimming interface	Remote Dimmable (Dimmer Not Included)