




# **Bellhop Floor**

Designed by Edward Barber and Jay Osgerby, 2020

26W - 1023Im - 2700K - CRI> 90

The Bellhop collection designed by Barber Osgerby expands with the introduction of an eccentric up-lit floor lamp. Originating from the Bellhop table lamp design, the designers have flipped the arched diffuser upside down and elongated the body to nearly 6ft high. Bellhop Floor is constructed from painted glass, aluminum, and an eco-friendly concrete base. Finishes: Floor Lamp Body /Diffuser Combo Brown Body / White Diffuser Green Body / White Diffuser Red Body / White Diffuser White Body / Grey Diffuser "Following the Bellhop portable and outdoor lamps, we decided to work on a floor-standing version, one that fits the collection but gives a totally different quality of light. While table lamps are often discreet and offer direct lighting, the new Bellhop Floor has a more sculptural character." - Edward Barber & Jay Osgerby




BOOK AN APPOINTMENT

# Main specifications

EAN	8059607039724	
Mounting	Floor	
Environments	Indoor dry location	
Light Source Type	LED	
Light sources included	Yes	
LED type	LED array	
Power (W)	26	
System power (W)	26	
System flux (lm)	1023	

## Physical

Color	Green
Length (in)	10.24
Cord color	Black
Cord length (in)	106.299
Net weight (lb)	21.66
Package volume (in)	2797.58
IP internal	20



Download	
Mounting instructions	<b>业</b> PDF
Mounting instructions	<b>业</b> PDF
Photometric Files LDT/IES	<u>↓</u> LDT
Technical Drawings	
3D	₹ ZIP

https://professional.flos.com/en-US/us/product/bellhop-floor-f1070039/

F1070039

















**Ecodesign and Energy** 

This product contains a light source of energy efficiency

Replaceable (LED only)

light source by a professional

Replaceable control gear by an end-user

Labelling

class G



# Schematic light drawing



Bean	n Angle:	33°
h(m)	E(lx)	D(m)
1	1474	0.59
2	368	1.19
3	164	1.78
4	92	2.38
-		0.07

h(m)	E(lx)	D(m
1	1474	0.5
2	368	1.1
3	164	1.7
4	92	2.3
5	59	2.9

### Photometric


Lighting type	Indirect	
Light distribution	Roto symmetric	
CCT (K)	2700	
CRI>	90	
Extreme cut off	No	

# Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
LED current (mA)	700
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Switch Integrated (Remote Dimmable)
Plug type	Type G, Type A, Type C
Batteries inside	No

https://professional.flos.com/en-US/us/product/bellhop-floor-f1070039/

# **Spare Parts**



01.	Bellhop Floor Reflector White	F1073009
02.	Bellhop Floor Base Concrete	F1072009
03.	Bellhop Floor Switch Dimmer	RF30216
	Assembly 700mA	
04.	Black plug assembly kit & 48V	RF6600130
	driver	
05.	Bellhop F Kit screws for base	RF1070100









F1073009

Bellhop Floor Reflector White

F1072009

Bellhop Floor Base Concrete

RF30216

Bellhop Floor Switch Dimmer Assembly 700mA RF6600130

Black plug assembly kit & 48V driver



RF1070100

Bellhop F Kit screws for base