

FLOS

03.2001.14BDA Black

Bon Jour Ø 45 Dali


Designed by Philippe Starck, 2016



Recessed luminaire with LED light source. Remote 220/240V power supply included. It is necessary to anticipate a space for accessing the driver.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	4.5
System power (W)	6
Source flux (lm)	524
Lumen Output (lm)	311

Physical

Colour	Black
Trim	Yes
Recessed depth (mm)	187
Bezel diameter (mm)	45
Net weight (kg)	0.13
Package volume (m3)	0.01
IP internal	20
IP external	44

Download

[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Rf fidelity index	90
Rg gamut index	99
LED Life / Failure Ratio	L80B20 >36000h (Tc=85°C)
Beam angle C0-180 (°)	19
Beam angle C90-270 (°)	19
UGR _L	<10

Electrical


Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Forward voltage (V)	11.5
LED current (mA)	400
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Accessories included (honeycomb and cross screening cylinder). Remote power supply to be installed in an accesible place.