



# Bon Jour Ø 45 Dali


Designed by Philippe Starck, 2015



Recessed luminaire with LED light source. Remote 110/240V power supply included. It is necessary to anticipate a space for accessing the driver.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



#### Main specifications

Mounting	Ceiling recessed
Enviroment	Indoor dry location
LED type	Power LED
Lamp category	LED
Number of heads	1
Power (W)	6
Source flux (lm)	542.53
System flux (lm)	335

#### Physical

Colour	Copper
Trim	No
Orientation	Fixed
Recessed depth (mm)	67
Length (mm)	45
Net weight (kg)	0.13
IP	20
IP external	44

## Download

Mounting instructions



#### Photometric Files

LDT / IES



## **Technical Drawings**

2D	<b>▼</b> ZIP
3D	<b>业</b> ZIP


















https://professional.flos.com/en/global/product/bon-jour-45-dali-03.2001.cu.da/

03.2001.CU.DA

## Schematic light drawing



Beam Angle:		24°
h(m)	E(lx)	D(m)
1	1556	0.43
2	389	0.85
3	173	1.28
4	97	1.71
5	62	2.14

Luminous flux luminaire

#### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	24
Beam angle C90-270 (°)	24

#### Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	110/240
LED current (mA)	500
Driver	Remote included
Dimmable	Yes
Dimming type Dimmable DALI	

#### Notes

Accessories included (honeycomb and cross screening cylinder). Remote power supply to be installed in an accesible place.