

FLOS

03.2003.CU.DA Copper

Bon Jour Ø 90 Dali


Designed by Philippe Starck, 2015



Recessed luminaire with LED light source. Remote 110/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	13.5
Source flux (lm)	1505
System flux (lm)	640

Physical

Colour	Copper
Trim	No
Orientation	Fixed
Recessed depth (mm)	155
Length (mm)	90
Net weight (kg)	0.53
IP internal	20
IP external	44

Download

[Mounting instructions](#) PDF

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	34
Beam angle C90-270 (°)	34

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	110/240
LED current (mA)	500
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable DALI 2

Notes

Pre-installation frame must be ordered separately

Accessories & Power Supply



REQUIRED Frame

08.8974.00

Pre-installation frame



OPTIONAL Accessory

08.8976.14

Honeycomb and cross screening
cylinder