

## Bon Jour Ø 90 Dali


Designed by Philippe Starck, 2016



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Semirecessed        |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 16                  |
| System power (W)       | 17.5                |
| Source flux (lm)       | 2093                |
| Lumen Output (lm)      | 607                 |

### Physical

|                     |        |
|---------------------|--------|
| Colour              | Copper |
| Trim                | Yes    |
| Orientation         | Fixed  |
| Recessed depth (mm) | 155    |
| Bezel diameter (mm) | 90     |
| Length (mm)         | 90     |
| Net weight (kg)     | 0.53   |
| Package volume (m3) | 0.01   |
| IP internal         | 20     |
| IP external         | 44     |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Ecodesign and Energy  
Labelling



Photometric

|                          |                               |
|--------------------------|-------------------------------|
| Lighting type            | Direct                        |
| Light distribution       | Symmetric                     |
| CCT (K)                  | 3000                          |
| CRI>                     | 90                            |
| LED Life / Failure Ratio | L80B50 > 55.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 44                            |
| Beam angle C90-270 (°)   | 44                            |

Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Frequency (Hz)      | 50/60                                    |
| Main voltage (Vac)  | 220-240                                  |
| Forward voltage (V) | 33.4                                     |
| LED current (mA)    | 400                                      |
| Power supply        | Remote included                          |
| Dimmable            | Yes                                      |
| Power supply type   | Dimmable DALI 2                          |
| Dimming range (%)   | 1-100                                    |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |

Notes

Pre-installation frame must be ordered separately

Accessories & Power Supply



REQUIRED  
Frame

08.8974.00

Pre-installation frame



OPTIONAL  
Accessory

08.8976.14

Honeycomb and cross screening  
cylinder for Bon Jour 90