



Bon Jour

Designed by Philippe Starck, 2015



13W - 811Im - 2700K - CRI> 90

Table lamp providing diffuse light. Injection moulded PMMA clear transparent base and diffuser. Edge Lighting technology light source. Power cord length 200 cm, with dimmer switch that provide ON-OFF functions and 10-100% light adjustment. Plugin power supply with interchangeable plugs.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8059607001158
Mounting	Table
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	13
System flux (lm)	811

Physical

Colour	Copper
Length (mm)	283
Cord colour	Grey
Cord length (mm)	2350
Net weight (kg)	1.65
Package volume (m3)	0.07
IP internal	20



Download

Mounting instructions	业 PDF
Mounting instructions	业 PDF
Spare Parts	⊥ PDF

Photometric Files

LDT / IES



Technical Drawings

2D	$\overline{\mathbf{A}}$	ZIP
3D	<u></u>	ZIP



















Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	90
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
LED voltage Vf (Vdc)	null
Power Supply	Remote included
Dimmable	Yes
Power Supply Type	Electronic 24V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Accessories & Power Supply









OPTIONAL

F1033000

Bon Jour Crown

OPTIONAL

F1033007

Bon Jour Crown

OPTIONAL

F1033030


Bon Jour Crown

OPTIONAL

1033088

Bon Jour Crown

Spare Parts



- 11. Top cover copper assembly F1031015
- 05. White plug assembly kit & 24V RF3320200 driver

DOWNLOAD





F1031015

Top cover copper assembly

RF3320200

White plug assembly kit & 24V driver