



FA100174122 Opal

# C-Me Round 70 Opal Rgb NEW




Designed by FLOS Outdoor, 2008



LED source included. Remote electric power supply with DMX 3chx350mA interface, to be ordered separately. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 200 mm cable and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Extra clear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT





# Main specifications

EAN	8054/9360494/
Mounting	In-ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	3
System power (W)	3.4

# Physical

Colour	Ораг
Orientation	Fixed
Net weight (kg)	0.43
Package height (mm)	134
Package width (mm)	134
Package length (mm)	83
IP internal	67
IP external	66

# Download





# **Ecodesign and Energy** Labelling



Replaceable (LED only) light source by a professional













https://professional.flos.com/en/global/product/c-me-round-70-opal-rgb-fa100174122/

FA100174122

#### Photometric

Light distribution	Symmetric
CCT (K)	RGB
Extreme cut off	No

#### Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DMX
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency	No

#### Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance'

Dimmable version on request

#### **Accessories & Power Supply**



# REQUIRED Power supply

F990B22A000

Power supply with DMX interface for RGB fixtures 36W/220÷240v-3CH x 350mA (3CH x 10 x 1W) DMX control allowed IP67 Class I Selv Eq.



### REQUIRED Accessory

FA101

Box for Installation C-Me Round 70/90



#### OPTIONAL Accessory

F990B13A000

DMX splitter 512



#### OPTIONAL Accessory

F990B10A000

DMX controller; dimmer switch for recessed box (60mm hole centres)



## OPTIONAL Accessory

F990B12A000

DMX cable - shielded twisted pair with 110 Ohm constant impedance



### OPTIONAL Accessory

F990B11A000

DMX controller; stand-alone/pc interface.