

FLOS

03.1247.DYB Matte White

C1 Double Spot Wall Large Ø 56

UPGRADE


Designed by Vincent Van Duysen, 2020



Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Wall surface |
| Environments | Indoor dry location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Power (W) | 28 |
| Source flux (lm) | 2799 |
| System flux (lm) | 2150 |

Physical

| | |
|--------------------------|-------------|
| Color | Matte White |
| Orientation | Adjustable |
| Rotation (°) | 180 |
| Longitudinal tilting (°) | 60 |
| IP internal | 20 |

Download

| | |
|-----------------------|-----|
| Family spec sheet | ZIP |
| Mounting instructions | PDF |

Photometric Files

| | |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

Technical Drawings

| | |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |




Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional

Schematic light drawing



Photometric

| | |
|--------------------------|------------------------------|
| Lighting type | Indirect, Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| Rf fidelity index | 91 |
| Rg gamut index | 98 |
| LED Life / Failure Ratio | L80B20 >36,000h (Tc=85°C) |
| Beam angle C0-180 (°) | 34 |
| Beam angle C90-270 (°) | 34 |


Electrical

| | |
|------------------|-----------------|
| Insulation class | III |
| LED current (mA) | 950-1200 |
| Driver | Remote excluded |
| Dimmable | Yes |

Notes

Photometric data without up diffuser.


Accessories & Power Supply



REQUIRED
Accessory

Installation


08.0226.00A9S
C1 Wall Large Double No Trim
Installation Frame



REQUIRED
Accessory

Installation

08.0254.00A9S
C1 Wall Large Double Surface
Flush accessory



REQUIRED
Power supply

Electrical

SP40W1200MA-10V-A01
Splice Box 40W, 1% dim, 0-10V,
1200mA 120/277V.