

# FLOS

03.1248.ESB Brushed Bronze

## C1 Double Spot Wall Large Ø 56 UPGRADE


Designed by Vincent Van Duysen, 2021



Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Wall surface
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Power (W)	28
Source flux (lm)	2799
System flux (lm)	2216

### Physical

Color	Brushed Bronze
Orientation	Adjustable
Rotation (°)	180
Longitudinal tilting (°)	60
IP internal	20

### Download

[Family spec sheet](#) ZIP

[Mounting instructions](#) PDF

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings

[2D](#) ZIP

[3D](#) ZIP




### Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

## Schematic light drawing



### Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Rf fidelity index	91
Rg gamut index	98
LED Life / Failure Ratio	L80B20 >36.000h (Tc=85°C)
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45

### Electrical

Insulation class	III
LED current (mA)	950-1200
Driver	Remote excluded
Dimmable	Yes

### Notes

Photometric data without up diffuser.

## Accessories & Power Supply




REQUIRED  
Accessory

Installation

08.0226.00A9S

C1 Wall Large Double No Trim  
Installation Frame




REQUIRED  
Accessory

Installation

08.0254.00A9S

C1 Wall Large Double Surface  
Flush accessory



REQUIRED  
Power supply

Electrical

SP40W1200MA-10V-A01

Splice Box 40W, 1% dim, 0-10V,  
1200mA 120/277V.