

FLOS

03.1250.DYB Matte White

C1 Mono Spot Ceiling Large Ø 56

UPGRADE

Designed by Vincent Van Duysen, 2020




14W - 1070lm - 2700K - CRI> 90 - Beam° 14

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Power (W)	14
Source flux (lm)	1321
System flux (lm)	1070

Physical

Color	Matte White
Orientation	Adjustable
Rotation (°)	355
Longitudinal tilting (°)	60
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files

LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP




Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Rf fidelity index	90
Rg gamut index	99
LED Life / Failure Ratio	L80B20 >36.000h (Tc=85°C)
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14

Electrical

Insulation class	III
LED current (mA)	950-1200
Driver	Remote excluded
Dimmable	Yes

Accessories & Power Supply



Ø 3.23"



REQUIRED
Accessory

Installation

08.0207.00A9S

C1 Ceiling Large No Trim
Installation Frame.



REQUIRED
Accessory

Installation

08.0212.DYA9S

C1 Ceiling Large Surface Mounted
Canopy



REQUIRED
Accessory

Installation

08.0212.DRA9S

C1 Ceiling Large Surface Mounted
Canopy



REQUIRED
Accessory

Installation

08.0212.ERA9S

C1 Ceiling Large Surface Mounted
Canopy



REQUIRED
Accessory

Installation

08.0212.ESA9S

C1 Ceiling Large Surface Mounted
Canopy




REQUIRED
Accessory

Installation

08.0212.EQA9S

C1 Ceiling Large Surface Mounted
Canopy




REQUIRED
Power supply

Electrical

SP40W1200MA-10V-A01

Splice Box 40W, 1% dim, 0-10V,
1200mA 120/277V.



REQUIRED
Power supply

Electrical

SP20W1200MA-PEQ-S01

Lutron EcoSystem Splice Box
20W, 1% dim, listed driver with
enclosure, 1200mA 120/277V.