

## C1 Mono Spot Wall Small Ø 35

Designed by Vincent Van Duysen, 2021




LED - Power LED - 6W - 368lm - 2700K - CRI> 90 - Beam° 18

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Wall surface        |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Power (W)              | 6                   |
| Lumen Output (lm)      | 368                 |

### Physical

|                          |                |
|--------------------------|----------------|
| Colour                   | Brushed Bronze |
| Orientation              | Adjustable     |
| Rotation (°)             | 180            |
| Longitudinal tilting (°) | 60             |
| Spot diameter (mm)       | 35             |
| Net weight (kg)          | 0.33           |
| IP internal              | 20             |
| IP external              | 20             |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 18        |
| Beam angle C90-270 (°) | 18        |
| Extreme cut off        | No        |
| UGR <sub>L</sub>       | <10       |

Electrical

|                  |                 |
|------------------|-----------------|
| Insulation class | III             |
| LED current (mA) | 500             |
| Power supply     | Remote excluded |
| Dimmable         | Yes             |
| Emergency        | No              |

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

60.9592  
Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA - 15W / 400mA - 17W / 450mA - 19W / 500mA - 22W / 550mA - 24W / 600mA - 26W / 650mA - 28W / 700mA - 30W.



REQUIRED  
Power supply  
Electrical

60.9208  
Continuous current power supply of 13-20W - Dim 1-10V&Push - 110/240V - 50/60Hz with power current selected through adjustable



REQUIRED  
Power supply  
Electrical

60.7678  
Continuous current supply source of 240V - 50/60Hz with dimmable Dali 2, Push dimming. 150mA - 7.8W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.6W / 350mA - 18.2W / 400mA - 20.8W / 500mA - 26W / 600mA - 31.2W / 700mA - 36.4W / 750mA - 39W / 800mA - 41.6...




REQUIRED  
Frame  
08.0206.00  
No Trim installation frame for wall mounting



REQUIRED  
Accessory  
08.0209.DR  
Coated aluminum mount for surface installation (wall)



REQUIRED  
Accessory  
08.0209.DY  
Coated aluminum mount for surface installation (wall)



REQUIRED  
Accessory  
08.0231.00  
Aluminum Mount for Surface Flush Installation (wall)



REQUIRED  
Accessory  
08.0209.EQ  
Coated aluminum mount for surface installation (wall)



REQUIRED  
Accessory

08.0209.ER

Coated aluminum mount for  
surface installation (wall)



REQUIRED  
Accessory

08.0209.ES

Coated aluminum mount for  
surface installation (wall)



REQUIRED  
Power supply

Electrical

60.9207

Casambi continuous current  
power supply, dimmable  
220/240V - 50/60Hz, 300mA -  
16W / 350mA - 18,5W / 400mA -  
21,5W / 450 mA - 24W / 500mA -  
27W / 600mA - 32W / 650 mA -  
35W / 700 mA - 36W /750 /800  
/900 /1000 /1050 /1200 mA -  
38W.