

C1 Mono Spot Wall Small Ø 35

Designed by Vincent Van Duysen, 2020




LED - Power LED - 6W - 382lm - 3000K - CRI> 90 - Beam° 15

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Wall surface
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Power (W)	6
System flux (lm)	382

Physical

Color	Anthracite
Orientation	Adjustable
Rotation (°)	180
Longitudinal tilting (°)	60
IP internal	20
IP external	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15
UGR _L	<10

Electrical

Insulation class	III
LED current (mA)	500
Driver	Remote excluded
Dimmable	Yes
Emergency type	No

Accessories & Power Supply



REQUIRED
Accessory

Installation

08.0206.00.9S
C1 Wall Small Mono No Trim
Installation Frame



REQUIRED
Accessory

Installation


08.0209.DY.9S
C1 Wall Small Mono Surface
Mounted Canopy



REQUIRED
Accessory

Installation

08.0209.DR.9S
C1 Wall Small Mono Surface
Mounted Canopy



REQUIRED
Accessory

Installation

08.0231.00.9S
C1 Wall Small Mono Surface Flush
accessory



REQUIRED
Accessory

Installation

08.0209.EQ.9S
C1 Wall Small Mono Surface
Mounted Canopy



REQUIRED
Accessory

Installation


08.0209.ER.9S
C1 Wall Small Mono Surface
Mounted Canopy



REQUIRED
Accessory

Installation


08.0209.ES.9S
C1 Wall Small Mono Surface
Mounted Canopy



REQUIRED
Power supply

Electrical

SP40W500MA-10V-A02
Splice Box 40W, 1% dim, 0-10V,
500mA 120/277V.



REQUIRED
Power supply

Electrical

SP20W500MA-PEQ-S01

Lutron EcoSystem Splice Box
20W, 1% dim, listed driver with
enclosure, 500mA, 120/277V.