

FLOS

 F011D20AU37 Burgundy Red

Captain Flint Outdoor B1

Designed by Michael Anastassiades, 2015



629lm - 2700K - CRI>80 - Beam° 112

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|------------------------|----------------------|
| EAN | 8054793214993 |
| Mounting | Ground |
| Environments | Outdoor wet location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | LED array |
| Number of lamps | 1 |
| System power (W) | 9.5 |
| Source flux (lm) | 989 |
| System flux (lm) | 629 |

Physical

| | |
|-------------------------|--------------|
| Color | Burgundy Red |
| Orientation | Adjustable |
| Transversal tilting (°) | 270 |
| Net weight (lb) | 4.92 |
| Package height (in) | 42.13 |
| Package width (in) | 18.11 |
| Package length (in) | 12.6 |
| Package volume (in) | 9611.52 |
| IP internal | 65 |



Download

Family spec sheet [ZIP](#)


Mounting instructions [ZIP](#)

Photometric Files


LDT / IES [ZIP](#)



Ecodesign and Energy Labelling



Schematic light drawing



| | | |
|------------------|-------------|-------------|
| Beam Angle: 114° | | |
| <u>h(m)</u> | <u>E(k)</u> | <u>D(m)</u> |
| 1 | 217 | 3.05 |
| 2 | 54 | 6.11 |
| 3 | 24 | 9.16 |
| 4 | 14 | 12.22 |
| 5 | 9 | 15.27 |

Luminous flux luminaire
629 lm

Photometric

| | |
|------------------------|-----------|
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 112 |
| Beam angle C90-270 (°) | 112 |
| Extreme cut off | No |

Electrical

| | |
|--------------------|--------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 110-277 |
| Driver | Integrated |
| Dimmable | No |
| Dimming interface | Not Dimmable |



REQUIRED Accessory

F018Z000000

Box for ground installation