



Captain Flint Outdoor B1

Designed by Michael Anastassiades, 2015

629lm - 2700K - CRI> 80 - Beam° 112



Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8054793215013	
Mounting	Ground	
Environments	Outdoor wet location	
Light Source Type	LED	
Light sources included	Yes	
LED type	LED array	
Number of lamps	1	
System power (W)	9.5	
Source flux (lm)	989	
System flux (lm)	629	

Physical

Color	Brass Finish
Orientation	Adjustable
Transversal tilting (°)	270
Net weight (lb)	4.92
Package height (in)	42.13
Package width (in)	18.11
Package length (in)	12.6
Package volume (in)	9611.52
IP internal	65



Download

Family spec sheet

✓ ZIP

Mounting instructions
✓ ZIP

Photometric Files

LDT / IES











Ecodesign and Energy Labelling





Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

https://professional.flos.com/en-US/us/product/captain-flint-outdoor-b1-f011d20au59/

F011D20AU59

Schematic light drawing



Beam	Angle:	114°
h(m)	E(lx)	D(m)
1	217	3.05
2	54	6.11
3	24	9.16
4	14	12.22
5	9	15.27

Luminous flux luminaire 629 lm

Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	112
Beam angle C90-270 (°)	112
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	110-277
Driver	Integrated
Dimmable	No
Dimming interface	Not Dimmable

Accessories & Power Supply



REQUIRED Accessory

F018Z000000

Box for ground installation