



Captain Flint Outdoor B1

Designed by Michael Anastassiades, 2015

652lm - 3000K - CRI> 80 - Beam° 112



Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8054793215396
Mounting	Ground
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
System power (W)	9.5
Source flux (lm)	1026
System flux (lm)	652

Physical

Color	Brass Finish
Orientation	Adjustable
Transversal tilting (°)	270
Net weight (lb)	4.92
Package height (in)	42.13
Package width (in)	18.11
Package length (in)	12.6
Package volume (in)	9611.52
IP internal	65



Download Family spec sheet

↓ ZIP

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

CERTIFIED







Ecodesign and Energy Labelling





Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

https://professional.flos.com/en-US/us/product/captain-flint-outdoor-b1-f011d30bu59/

F011D30BU59

Schematic light drawing



Beam	Angle:	114°
h(m)	E(lx)	D(m)
1	225	3.05
2	56	6.11
3	25	9.16
4	14	12.22
5	9	15.27

Luminous flux luminaire 652 lm

Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	112
Beam angle C90-270 (°)	112
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	110-127
Driver	Integrated
Driver Dimmable	Integrated Yes

Accessories & Power Supply



REQUIRED Accessory

F018Z000000

Box for ground installation