



F011A42F030.A Black/Black Lava

Captain Flint Outdoor H 1537 mm Black/Black

Designed by Michael Anastassiades, 2017

744lm - 4000K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793212951
Mounting	Floor
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	LED array
System power (W)	11
Source flux (lm)	1221
Lumen Output (lm)	744

Physical

Colour	Black/Black Lava	
Trim	No	
Orientation	Adjustable	
Transversal tilting (°)	270	
Net weight (kg)	14.35	
IP internal	65	

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	⊥ ZIP
3D	⊥ ZIP
∄Bim	<u>↓</u> ZIP

https://professional.flos.com/en/global/product/captain-flint-outdoor-h-1537-mm-black-black-lava-f011a42f030.a/

F011A42F030.A

Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	263	2.95
2	66	5.91
3	29	8.86
4	16	11.81
5	11	14.76

Direct

4000

80

110

110

No

Symmetric

30°	/ 263 cc	7 k	_30°
Lumir	nous flux	lur	ninaire
711 ~			

Photometric

Beam angle C0-180 (°)

Beam angle C90-270

Extreme cut off

Lighting type

CCT (K)

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmer on board
Dimming interface	Switch Integrated (Remote Dimmable)
Emergency	No

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional