

# FLOS



F011A23F059.A Brass Finish/Grey Lava

## Captain Flint Outdoor H 1537 mm Brass Finish/Grey Lava

Designed by Michael Anastassiades




LED - LED array - 11W - 669lm - 2700K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Floor
Environments	Outdoor wet location
LED type	LED array
Lamp category	LED
Iicos	No
Power (W)	11
Source flux (lm)	1099
System flux (lm)	669

### Physical

Colour	Brass Finish/Grey Lava
Trim	No
Orientation	Adjustable
Transversal tilting (°)	270
Net weight (kg)	10
IP internal	65

### Download

[Mounting instructions](#)  ZIP


### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



## Schematic light drawing



Beam Angle: 112°

h(m)	E(lx)	D(m)
1	237	2.95
2	59	5.91
3	26	8.86
4	15	11.81
5	9	14.76

Luminous flux Luminaire  
669 lm

## Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110
Extreme cut off	No

## Electrical


Insulation class	II
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Power Supply	Remote included
Dimmable	Yes
Power Supply Type	Dimmer on board
Emergency type	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only)  
light source by a  
professional



Replaceable control  
gear by an end-user