

FLOS



F011A23F059.A Brass Finish/Grey Lava

Captain Flint Outdoor H 1537 mm Brass Finish/Grey Lava

Designed by Michael Anastassiades, 2017




669lm - 2700K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793209630
Mounting	Floor
Environments	Indoor Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	LED array
System power (W)	11
Source flux (lm)	1099
System flux (lm)	669

Physical

Colour	Brass Finish/Grey Lava
Trim	No
Orientation	Adjustable
Transversal tilting (°)	270
Net weight (kg)	14.35
IP internal	65

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Beam Angle: 112°

h(m)	E(lx)	D(m)
1	237	2.95
2	59	5.91
3	26	8.86
4	15	11.81
5	9	14.76

Luminous flux Luminaire
669 lm


Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110
Extreme cut off	No


Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmer on board
Dimming interface	Switch Integrated (Remote Dimmable)
Emergency	No

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional