



Captain Flint Outdoor W1


Designed by Michael Anastassiades, 2015



Luminaire for wall-mounting with diffuse light emission and fixed head. LED light source included. Integrated 220-240V ON/OFF or 1-10V/DALI dimmable electrical power. Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included. 110V version upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793217376	
Mounting	Wall	
Environments	Outdoor wet location	
Light source type	LED	
Light sources included	Yes	
LED type	LED array	
Number of lamps	1	
System power (W)	9.5	
Source flux (lm)	1099	
Lumen Output (lm)	699	

Physical

Colour	Deep Brown
Trim	No
Orientation	Fixed
Spot diameter (mm)	208
Length (mm)	336
Net weight (kg)	2.1
Package height (mm)	257
Package width (mm)	406
Package length (mm)	406
Package volume (m3)	0.04
IP internal	65

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

<u>↓</u> ZIP

Technical Drawings

2D	⊥ ZIP
3D	⊥ ZIP
₿Bim	⊥ ZIP

https://professional.flos.com/en/global/product/captain-flint-outdoor-w1-f011w40a018/

F011W40A018

Schematic light drawing



Beam Angle:		114°
h(m)	E(lx)	D(m)
1	242	3.05
2	60	6.11
3	27	9.16
4	15	12.22
5	10	15.27

Luminous flux luminaire

Photometric

Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	112
Beam angle C90-270 (°)	112

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Non Dimmable
Precabled	NO
Emergency	No
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

110V version upon request.