



F016A21BU33 Anthracite

Caule Bollard 1 Dimmable 1-10V NEW

Designed by Patricia Urquiola, 2019



Caule by Patricia Urquiola is an outdoor collection featuring both in-ground bollards and plug-in floor fixtures with two diffuser options a mesh, nest head and or solid head. Taking after its name, Caule embodies the structure of a flower and its stem. Its natural form blends seamlessly into the environment around, creating intriguing shadows and highlighting outdoor pathways." Caule is an outdoor collection with simple understated lines yet strong style identity. Copying the botanical structure of a flower, the collection features a real flexible slender stem, almost a natural element, a subtle addition to any outdoor setting." - Patricia Urquiola



BOOK AN APPOINTMENT

Main specifications

EAN	8054793241135	
Mounting	Ground	
Environments	Outdoor wet location	
Light Source Type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	f lamps 1	
Power (W)	5	
System power (W)	5	
System flux (lm)	282	

Physical

Color	Anthracite
Orientation	Fixed
Net weight (lb)	8.16
Package height (in)	5.91
Package width (in)	39.37
Package length (in)	19.68
Package volume (in)	4576.8
IP internal	66

Download

Dominoda		
Family spec sheet	₹ ZIP	
Mounting instructions	₹ ZIP	

Photometric Files

31.

LDT / IES



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



https://professional.flos.com/en-US/us/product/caule-bollard-1-dimmable-1-10v-f016a21bu33/

F016A21BU33

Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	332	0.98
2	83	1.96
3	37	2.94
4	21	3.92
5	13	4.90

Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	52
Beam angle C90-270 (°)	52
Extreme cut off	No

Electrical

Insulation class	I	
Frequency (Hz)	50/60	
Main voltage (Vac)	120-277	
Driver	Integrated	
Dimmable	Yes	
Dimming range (%)	nming range (%) 10-100	
Dimming interface	Dimmer Integrated	
Emergency type	No	

Notes

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Accessories & Power Supply



OPTIONAL Accessory

F016Z000000

Box for ground installation