



FA94831206-300 Grey

Cielo L 645 Dimmable Dali NEW




Designed by FLOS Outdoor, 2007



LED source included. Integrated power supply 220-240V ON/OFF and dimmable 1-10V or DALI. Adjustment on the vertical axis: max. 12°. The necessary junction box or the structure for plasterboard installation need to be ordered separately. With two M20 cable guides (6<ø<12mm cables) for the connection to the watertight electrical module. Extraclear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793697222
Mounting	In-ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	13
System power (W)	16
Source flux (lm)	1440
Lumen Output (lm)	1314

Physical


Colour	Grey
Orientation	Adjustable
Transversal tilting (°)	12
Net weight (kg)	3.15
Package height (mm)	120
Package width (mm)	110
Package length (mm)	835
Package volume (m3)	0.01
IP internal	67
IP external	66

Download Mounting instructions	⊥ ZIP
Photometric Files	⊥ ZIP
Technical Drawings	1
2D 3D	₹ ZIB

https://professional.flos.com/en/global/product/cielo-l-645-dimmable-dali-fa94831206-300/

FA94831206-300

Schematic light drawing



Ве	am Ang	jle:	14°
h(r	n) E(l	x)	D(m)
1_	1470	2	0.24
2	367	6	0.48
3	163	4	0.72
4	91	9	0.96
5	58	8	1.20

14702 cd
Luminous flux luminaire
19141111

Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12
Extreme cut off	No

Electrical

Insulation class	T
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Dimmable Power supply type	Yes Dimmable DALI 1

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional


Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply







REQUIRED Accessory

FA71

Box for Installation Cielo L 645 mm

REQUIRED Accessory

FA81

Frame For Ceiling Recessed Installation Cielo L 645

OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)