



FA9418613133 Anthracite

Cielo L 645 NEW




Designed by FLOS Outdoor, 2007



LED source included. Integrated power supply 220-240V ON/OFF and dimmable 1-10V or DALI. Adjustment on the vertical axis: max. 12°. The necessary junction box or the structure for plasterboard installation need to be ordered separately. With two M20 cable guides (6<ø<12mm cables) for the connection to the watertight electrical module. Extraclear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793696102
Mounting	In-ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	13
System power (W)	16
Source flux (lm)	1560
Lumen Output (lm)	1251

Physical

Colour	Anthracite
Orientation	Adjustable
Transversal tilting (°)	12
Net weight (kg)	3.15
Package height (mm)	120
Package width (mm)	110
Package length (mm)	835
Package volume (m3)	0.01
IP internal	67
IP external	66

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	⊥ ZIP
3D	↓ ZIP







https://professional.flos.com/en/global/product/cielo-l-645-fa9418613133/

FA9418613133

Schematic light drawing



E	3ean	n Angle	: 12
ŀ	n(m)	E(lx)	D(m
	1	4597	0.22
2	2	1149	0.43
-	3	511	0.65
4	1	287	0.87
	_	104	1.00

Photometric

Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Extreme cut off	No

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Discondina	
Dimmable	No
Power supply type	Non Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional


Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply







REQUIRED Accessory

FA71

Box for Installation Cielo L 645 mm

REQUIRED Accessory

FA81

Frame For Ceiling Recessed Installation Cielo L 645

OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)