



FA941861333 Anthracite

Cielo L 645 NEW




Designed by FLOS Outdoor, 2007



LED source included. Integrated power supply 220-240V ON/OFF and dimmable 1-10V or DALI. Adjustment on the vertical axis: max. 12°. The necessary junction box or the structure for plasterboard installation need to be ordered separately. With two M20 cable guides (6<ø<12mm cables) for the connection to the watertight electrical module. Extraclear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

EAN	8054793696133
Mounting	In-ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	13
System power (W)	16
Source flux (lm)	1560
Lumen Output (lm)	1248

## Physical

Colour	Anthracite
Orientation	Adjustable
Transversal tilting (°)	12
Net weight (kg)	3.15
Package height (mm)	120
Package width (mm)	110
Package length (mm)	835
Package volume (m3)	0.01
IP internal	67
IP external	66

# Download





### Photometric Files

LDT / IES



## **Technical Drawings**

2D	<b>↓</b> ZIP
3D	<u>↓</u> ZIP

https://professional.flos.com/en/global/product/cielo-l-645-fa941861333/

FA941861333

## Schematic light drawing



Bear	m Angle:	45
h(m)	E(lx)	D(n
1	2008	0.8
2	502	1.6
3	223	2.4
4	126	3.2
5	80	4.0

#### Photometric

Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	44
Beam angle C90-270 (°)	44
Extreme cut off	No

#### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	
5111110010	No
Power supply type	Non Dimmable

## **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

#### **Notes**

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

## **Accessories & Power Supply**







REQUIRED Accessory

FA71

Box for Installation Cielo L 645 mm

REQUIRED Accessory

FA81

Frame For Ceiling Recessed Installation Cielo L 645

#### OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)