



Clessidra 40°+40°

Designed by Antonio Citterio, 2011



10W - 601lm - 3000K

Diffused direct/indirect-light wall lighting device. Body obtained by means of aluminium pressofusion and diffusers in PMMA. Aluminium wall attachment with cover in PA66. Available in white-painted or chrome-plated for indoor version and dark brown-painted or dark gray-painted for outdoor version. High-efficiency lenses specially designed for the application, non-replaceable. Wide range (100-240Volt) power pack integrated in the body. Level IP55

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607001530
Mounting	Wall
Environments	Indoor wet location
Light source type	LED
Light sources included	Yes
LED type	LED array
Power (W)	10
Lumen Output (lm)	601

Physical

Colour	Grey	
Length (mm)	76	
Net weight (kg)	1.1	
IP internal	55	

Download

Mounting instructions	⊥ PDF
Spare Parts	↓ PDF

Photometric Files

LDT / IES



Technical Drawings

2D	<u>↓</u> ZIP
3D	↓ ZIP

















https://professional.flos.com/en/global/product/clessidra-4040-f1584006/

F1584006

Schematic light drawing



Beam Angle: - 40°		
h(m)	E(lx)	D(m)
1	488	0.56
2	122	1.13
3	54	1.69
4	31	2.26
5	20	2.82

189 ça 7 45"	
uminous flux l uminaire 35 lm	

Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Batteries inside	No
Charging min time	NO

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Spare Parts



01. Clessidra Wall attachment and F1582030 internal lamp body 40°+40°

02. Grey external clessidra lamp F158000 body

O3. Screws and tool kit for clessidra RF1580100 external lamp body

DOWNLOAD





internal lamp body 40°+40°



F1580006 Grey external clessidra lamp body



RF1580100 Screws and tool kit for clessidra external lamp body