



F1840044 Anodized Champagne


## Coordinates Ceiling 4 CLIII

Designed by Michael Anastassiades, 2020



147W - 8830lm - 2700K - CRI> 95

Coordinates is a lighting system with diffuse light composed of horizontal and vertical luminaries arranged in a bright grid of various shapes and complexities. Each element is made of extruded anodized aluminium with a champagne finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 95). Each element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the 1 ceiling models C4, Its geometry was designed to be repeated to create large grids for custom installations. Each Coordinates configuration must include its own ceiling rose, whose integrated electronics allow for the use of different dimmer systems: push, 1-10, DALI. In the absence of these systems, the amount of light can be set during installation with the push system included in the rose. The related CI III version is also available for each configuration for installations with a remote power supply.



Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 

#### Main specifications

EAN	8059607033203	
Mounting	Ceiling	
Environments	Indoor dry location	
Light source type	LED	
Light sources included	Yes	
LED type	LED Module	
Power (W)	147	
Lumen Output (lm)	8830	

#### **Physical**

Colour	Anodized Champagne	
Length (mm)	1770	
Net weight (kg)	5.2	
Package volume (m3)	0.05	
IP internal	20	

<b>业</b> PDF
<b>⊥</b> ZIP
j
<b>⊥</b> ZIP
<b>⊥</b> ZIP

https://professional.flos.com/en/global/product/coordinates-ceiling-4-cliii-f1840044/

F1840044

















#### Photometric

Lighting type	Total	
Light distribution	Asymmetric	
CCT (K)	2700	
CRI>	95	
Extreme cut off	No	

#### Electrical

Insulation class	III	
Main voltage (Vac)	48	
Power supply	Remote excluded	
Power supply type	Electronic 48V	
Batteries inside	No	

# Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F** 



Replaceable (LED only)
light source by a professional

https://professional.flos.com/en/global/product/coordinates-ceiling-4-cliii-f1840044/

### **Accessories & Power Supply**





**OPTIONAL** 

RF26994

12-48V Led Dimmer

OPTIONAL

RF29209

48Vdc 180W Power supply



00.	Rod Assembly L920 C-09	RF30993
	Anodized Champagne	
00.	Coordinates Ceiling 4 Rod	RF30992
	Assembly L920 C-08 Anodized	
	Champagne	
00.	Coordinates Rod Assembly	RF30984
	L1760 H-10 Anodized	
	Champagne	
00.	Coordinates Rod Assembly	RF30985
	L1760 H-11 Anodized	
	Champagne	



RF30993

Rod Assembly L920 C-09 Anodized Champagne RF30992

Coordinates Ceiling 4 Rod Assembly L920 C-08 Anodized Champagne RF30984

Coordinates Rod Assembly L1760 H-10 Anodized Champagne RF30985

Coordinates Rod Assembly L1760 H-11 Anodized Champagne