



### **Coordinates Suspension 2**

Designed by Michael Anastassiades, 2020



55W - 2960lm - 2700K - CRI> 95

Coordinates is a lighting system with diffuse light composed of horizontal and vertical luminaries arranged in a bright grid of various shapes and complexities. Each element is made of extruded anodized aluminium with a champagne or argent finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 95). Each element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the 4 hanging models (S1, S2, S3, S4) with 2.4-m cables. Each Coordinates configuration includes its own ceiling rose, whose integrated electronics allow for the use of different dimmer systems: push, 1-10, DALI. In the absence of these systems, the amount of light can be set during installation with the push system included in the rose.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

#### Main specifications

EAN	8059607038345 Suspension	
Mounting		
Environments	Indoor dry location	
Light source type	LED	
Light sources included	Yes	
LED type	LED Module	
Power (W)	55	
Lumen Output (lm)	2960	

#### **Physical**

Colour	Argent
Length (mm)	1760
Cord colour	Clear
Cord length (mm)	2400
Canopy colour	Argent
Canopy length/diameter (mm)	149
Canopy height (mm)	71
Net weight (kg)	2.7
Package volume (m3)	0.03
IP internal	20



# Download Mounting instructions

Photometric Files

, PDF

**↓** ZIP



3D <u>★</u> ZIP ★ Bim ★ ZIP

https://professional.flos.com/en/global/product/coordinates-suspension-2-f1862033/

F1862033





















#### Photometric

Lighting type	Total	
Light distribution	Asymmetric	
CCT (K)	2700	
CRI>	95	
Extreme cut off	No	

#### Electrical

Insulation class	1	
Frequency (Hz)	50/60	
Main voltage (Vac)	120-240	
Power supply	Integrated	
Dimmable	Yes	
Power supply type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1	
Dimming interface	Dimmable Push, Dimmable 1-10V,	

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F** 




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

#### **Spare Parts**



01.	Power supply kit for	RF0410500
	Arrangements small &	
	Noctambule	
02.	Led dimmer kit	RF34197
03.	Assembly Rose for Coordinates	RF1872133
	Suspension Argent	
04.	Coordinates Suspension 2 Rod	RF30927
	Assembly L920 SA-19 Argent	
05.	Coordinates Suspension 2 Rod	RF30929
	Assembly 1760 H-21 Argent	
06.	Coordinates Suspension 2 Rod	RF30928
	Assembly L920 S-20 Argent	









RF0410500

Power supply kit for Arrangements small & Noctambule RF34197

Led dimmer kit

RF1872133

Assembly Rose for Coordinates Suspension Argent

RF30927

Coordinates Suspension 2 Rod Assembly L920 SA-19 Argent

.



RF30929

Coordinates Suspension 2 Rod Assembly 1760 H-21 Argent RF30928

Coordinates Suspension 2 Rod Assembly L920 S-20 Argent