



Coordinates Suspension 3

Designed by Michael Anastassiades, 2020



71W - 3850lm - 2700K - CRI> 95

Coordinates is a lighting system with diffuse light composed of horizontal and vertical luminaries arranged in a bright grid of various shapes and complexities. Each element is made of extruded anodized aluminium with a champagne or argent finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 95). Each element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the 4 hanging models (S1, S2, S3, S4) with 2.4-m cables. Each Coordinates configuration includes its own ceiling rose, whose integrated electronics allow for the use of different dimmer systems: push, 1-10, DALI. In the absence of these systems, the amount of light can be set during installation with the push system included in the rose.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8059607038369		
Mounting	Suspension		
Environments	Indoor dry location		
Light source type	LED		
Light sources included	Yes		
LED type	LED Module		
Power (W)	71		
System flux (lm)	3850		

Physical

Colour	Argent
Length (mm)	780
Cord colour	Clear
Cord length (mm)	2400
Canopy colour	Argent
Canopy length/diameter (mm)	149
Canopy height (mm)	71
Net weight (kg)	3.2
Package volume (m3)	0.04
IP internal	20



Download

Mounting instructions



Photometric Files

ULD



Technical Drawings



https://professional.flos.com/en/global/product/coordinates-suspension-3-f1850033/





















Photometric

Lighting type	Total	
Light distribution	Asymmetric	
CCT (K)	2700	
CRI>	95	
Extreme cut off	No	

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Spare Parts



00.	Rod Assembly L780 SA-01 Agent	RF30909
01.	Power supply kit for	RF0410500
	Arrangements small &	
	Noctambule	
03.	Assembly Rose for Coordinates S	RF1872133
	Argent	
04.	Rod Assembly L780 SA-01 Agent	RF30911





Rod Assembly L780 SA-01 Agent



RF0410500

Power supply kit for Arrangements small & Noctambule



RF1872133

Assembly Rose for Coordinates S Argent

RF30911

Rod Assembly L780 SA-01 Agent