




Coordinates Suspension 4

Designed by Michael Anastassiades, 2020



161W - 8830lm - 2700K - CRI> 95

Coordinates is a lighting system with diffuse light composed of horizontal and vertical luminaries arranged in a bright grid of various shapes and complexities. Each element is made of extruded anodized aluminium with a champagne or argent finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 95). Each element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the 4 hanging models (S1, S2, S3, S4) with 2.4-m cables. Each Coordinates configuration includes its own ceiling rose, whose integrated electronics allow for the use of different dimmer systems: push, 1-10, DALI. In the absence of these systems, the amount of light can be set during installation with the push system included in the rose.



Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8059607038383
Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	161
System flux (lm)	8830

Physical

Colour	Argent
Length (mm)	1762
Cord colour	Clear
Cord length (mm)	2400
Canopy colour	Argent
Canopy length/diameter (mm)	181
Canopy height (mm)	95
Net weight (kg)	7.9
Package volume (m3)	0.06
IP internal	20



https://professional.flos.com/en/global/product/coordinates-suspension-4-f1854033/

F1854033





















Photometric

Lighting type	Total
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



O1. Assembly Rose for Coordinates RF1873133
S4 Argent
O5. Rod Assembly L920 SA-12 Agent RF30922
O6. Rod Assembly L920 SA-12 Agent RF30920







RF1873133

Assembly Rose for Coordinates S4 Argent

RF3092

Rod Assembly L920 SA-12 Agent

RF30920

Rod Assembly L920 SA-12 Agent