



Coordinates Suspension 4

Designed by Michael Anastassiades, 2020



161W - 8830lm - 2700K - CRI> 95

Coordinates is a lighting system consisting of horizontal and vertical strip lights that form illuminated grid-like structures of various complexities. This collection of standard chandeliers of pared-down configurations that can be used in any setting. Each suspended element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the four hanging models (S1, S2, S3, S4). The S Module is also available to create semicustom designs for large-scale installations. Behind the design: This design evolved from a commission for the feature lighting of the main dining area of the historic Four Seasons restaurant in New York City. The restaurant relocated and opened in 2018 with the interiors designed by São Paolo-based architect Isay Weinfeld.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

| Mounting | Suspension |
|------------------------|---------------------|
| Environments | Indoor dry location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | LED Module |
| Power (W) | 161 |
| System flux (lm) | 8830 |

Physical

| Color | Argent |
|--------------------------------|---------|
| Length (in) | 69.68 |
| Cord color | Black |
| Cord length (in) | 94.488 |
| Canopy color | Argent |
| Canopy lenght/diameter (in) | 7.126 |
| Canopy height (in) | 3.740 |
| Net weight (lb) | 17.42 |
| Package volume (in) | 3827.42 |
| IP internal | 20 |



| Down | load |
|------|------|
| | loau |

Mounting instructions



Photometric Files

ULD



Technical Drawings

3[



https://professional.flos.com/en-US/us/product/coordinates-suspension-4-fu185433/









Photometric

| Lighting type | Total |
|--------------------|------------|
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 95 |
| Extreme cut off | No |

Electrical

| Insulation class | I |
|--------------------|---|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 100-240 |
| Driver | Integrated |
| Dimmable | Yes |
| Dimming type | Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



O1. Assembly Rose for Coordinates RF1873133S4 Argent

05. Rod Assembly L920 SA-12 Agent RF30922

https://professional.flos.com/en-US/us/product/coordinates-suspension-4-fu185433/

FU185433





RF1873133

Assembly Rose for Coordinates S4 Argent

RF30922

Rod Assembly L920 SA-12 Agent