

# FLOS

05.7036.GL Gold

## Easy Kap Ø 105 Adjustable

Designed by FLOS Architectural, 2019



'Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED
Lamp type	PAR16
Lamp holders	GZ10
Ilcos	No
Number of heads	1
System power (W)	4.2

### Physical

Colour	Gold
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	125
Spot diameter (mm)	111
Net weight (kg)	0.45
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54
IP external	54



### Download


[Mounting instructions](#)



### Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



## Photometric

Lighting type	Direct
Light distribution	Symmetric

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	230
LED current (mA)	-9
Emergency type	No

## Notes

Not suitable for lens accessories.

---