

# FLOS

05.7030.B1 White

## Easy Kap Ø 105 Fixed EVO

Designed by FLOS Architectural, 2019



Recessed 12V lamp luminaire. Remote transformer not included. Installation frame not necessary.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Ilcos	No

### Physical

Colour	White
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	134
Spot diameter (mm)	111
Net weight (kg)	0.23
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54
IP external	54



### Download


Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


[Bim](#) [↓ ZIP](#)



### Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Replaceable control gear by a professional

## Photometric

Lighting type	Direct
Light distribution	Symmetric

## Electrical

Insulation class	II
Frequency (Hz)	0
Forward voltage (V)	12
Driver	Remote excluded
Dimming type	Electronic 12V
Emergency type	No

## Notes

Not suitable for lens accessories.

---

## Accessories & Power Supply



OPTIONAL  
Power supply

Electrical

60.9424

12V Electronic Transformer 35-105W



OPTIONAL  
Power supply

Electrical

60.9398

12V Electronic Transformer 20-70W