

FLOS

05.7031.74 Black

Easy Kap Ø 105 Fixed EVO

Designed by FLOS Architectural, 2019



'Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED
Lamp type	PAR16
Lamp holders	GZ10
Ilcos	No
Number of heads	1
System power (W)	4.2

Physical

Colour	Black
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	155
Spot diameter (mm)	111
Net weight (kg)	0.23
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54
IP external	54



Download

[Mounting instructions](#)  PDF

Photometric Files


[LDT / IES](#)  ZIP

Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user

Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	230
LED current (mA)	-9
Emergency type	No

Notes

Not suitable for lens accessories.
