

Easy Kap Ø30 Adjustable Set of 4 spots Non-IC

Designed by FLOS Architectural, 2023

LED - Power LED - 4 x 2.5W - 4 x 187lm - 3000K - CRI> 95 - Beam° 51

NON-IC Ceiling Recessed Trimless Downlight. Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Class 2



Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	4
Power (W)	2.5
Source flux (lm)	229
System flux (lm)	187

Physical


Color	White
Trim	Yes
Orientation	Adjustable
Longitudinal tilting (°)	17
Transversal tilting (°)	17
Length (in)	1.4
IP internal	20
IP external	54




Download

Family spec sheet	ZIP
Mounting instructions	PDF

Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	95
McAdam steps (SDCM)	3
Rf fidelity index	95
Rg gamut index	104
LED Life / Failure Ratio	L90B50>51.000h_Tc85°C
Beam angle C0-180 (°)	51
Beam angle C90-270 (°)	51
Extreme cut off	No
UGR _L	<19

Electrical

Forward voltage (V)	3.3
LED current (mA)	900
Driver	Remote excluded
Dimming type	Non Dimmable, Dimmable DALI 2, Dimmable 1-10V, Mains Cut Dimming
Dimming interface	Remote Dimmable (Dimmer Not Included)

Accessories & Power Supply




REQUIRED
Power supply
Electrical

LEDSB40W800MA-V-Y1
LED DVR Variable Dim Triac, ELV,
40W, 800mA ,120/277V.



REQUIRED
Power supply
Electrical

SP12W850MA-DAL-T01
Splice Box UL 7"x3-5/8"x1-1/4",
With Eldoled Eco Drive Driver
Programmed to 850mA,12WDALI
Dimmable, 120-277V.



REQUIRED
Power supply
Electrical

SP12W850MA-10V-T01
Splice Box UL 7"x3-5/8"x1-1/4",
With Eldoled Eco Drive Driver
Programmed to 850mA, 12W, 0-
10V Dimmable, 120-277V.