

# FLOS

03.4160.B1 White

## Easy Kap Ø 80 Adjustable


Designed by FLOS Architectural, 2016



Recessed 12V lamp luminaire. Remote transformer not included. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Ilcos	No
Number of heads	1

### Physical

Colour	White
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	130
Spot diameter (mm)	80
Net weight (kg)	0.12
IP internal	20
IP external	23

### Download


[Mounting instructions](#)




### Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Replaceable control gear by a professional



## Photometric

Lighting type	Direct
Light distribution	Symmetric

## Electrical

Insulation class	III
Frequency (Hz)	0
Forward voltage (V)	12
LED current (mA)	-9
Driver	Remote excluded
Dimmable	No
Dimming type	Electronic 12V
Emergency type	No

## Notes

Not suitable for lens accessories.

---

## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.9424

12V Electronic Transformer 35-105W



REQUIRED  
Power supply

Electrical

60.9398

12V Electronic Transformer 20-70W