

FLOS

03.4172.GLUQ Gold

Easy Kap Ø 80 Adjustable Optic Flood - Non IC


Designed by FLOS Architectural, 2016



Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | LED array |
| Number of lamps | 1 |
| Power (W) | 9.2 |
| Source flux (lm) | 956 |
| System flux (lm) | 694 |
| Efficacy (lm/W) | 75 |

Physical

| | |
|--------------------------|------------|
| Color | Gold |
| Trim | Yes |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 20 |
| Transversal tilting (°) | 20 |
| Net weight (lb) | 7.77 |
| IP internal | 54 |

Download

[Family spec sheet](#)  ZIP


[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  ZIP




Accessories & Power Supply



REQUIRED Power supply

SP14W500MA-ELV-E01


Splice Box 9"x2"x1.5", 500mA ,
14W, ELV Dimmable, Thermal
120V



REQUIRED Power supply

SP20W500MA-120-V01

Splice Box 9"x2"x1.5", 500mA ,
20W, 0-10V , Dimmable, Thermal
120V




REQUIRED Power supply

Electrical

SP20W500MA-277-V01

Splice Box 9" x 2" x 1.5", 500mA,
20W, 0-10V, 277V



OPTIONAL Housing and Hanger Bar

TRAY-0001

Registration Tray - non electrical,
place holder for non IC new
construction, Ø2.95"