

FLOS

03.4211.74 Black

Easy Kap Ø 80 Fixed

Designed by FLOS Architectural, 2016



'Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|-------------------|---------------------|
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| Light Source Type | Bulb |
| Lamp category | LED retrofit |
| Lamp type | PAR16 |
| Lamp holders | GU10 |
| Ilcos | No |
| Number of heads | 1 |
| System power (W) | 50 |

Physical

| | |
|---------------------|-------|
| Colour | Black |
| Trim | Yes |
| Orientation | Fixed |
| Recessed depth (mm) | 155 |
| Spot diameter (mm) | 80 |
| Net weight (kg) | 0.12 |
| IP internal | 20 |
| IP external | 23 |



Download


Mounting instructions



Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Photometric

| | |
|--------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |

Electrical

| | |
|--------------------|-------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 230 |
| LED current (mA) | -9 |
| Emergency type | No |

Notes

Not suitable for lens accessories.
