


Easy Kap Ø 80 Fixed IP65 Optic Spot- Non IC

NEW

Designed by FLOS Architectural, 2025



LED luminaire for recessed mounting into plasterboard ceilings. The Easy Kap IP 65 version has an aluminium injected body with a liquid paint, dust finish with a plastic diffuser included. It does not need a pre-installation frame. Its LED Array have cutting-edge technology that permits a lower average temperature in the electronics and offer maximum quality light, the perception of objects and spaces, reaching chromatic reproduction indices of 90. Thanks to this feature, the luminaire can operate at a higher power inside the safety parameters yet still offering high luminous flux. IP 65 with lens. Power supply not included.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	9.2
Source flux (lm)	908
System flux (lm)	628

Physical

Color	Black
Trim	Yes
Recessed depth (in)	3.58
Spot diameter (in)	4.96
Length (in)	4.96
Net weight (lb)	0.53
IP internal	20
IP external	65

Download

- Family spec sheet
- Mounting instructions
- ZIP
- PDF

Photometric Files


- LDT / IES
- ZIP

Technical Drawings

- 2D
- 3D
- ZIP
- ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	19
Beam angle C90-270 (°)	19
Extreme cut off	No
UGR _L	<16

Electrical

Forward voltage (V)	18.2
LED current (mA)	500
Driver	Remote excluded
Dimmable	Yes

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Class 2 Listed

Accessories & Power Supply



REQUIRED
Power supply

SP14W500MA-ELV-E01
Splice Box 9"x2"x1.5", 500mA ,
14W, ELV Dimmable, Thermal
120V




REQUIRED
Power supply

SP20W500MA-120-V01
Splice Box9"x2"x1.5", 500mA ,
20W, 0-10V , Dimmable, Thermal
120V



REQUIRED
Power supply

Electrical
SP20W500MA-277-V01
Splice Box 9" x 2" x 1.5", 500mA,
20W, 0-10V, 277V



OPTIONAL
Housing and Hanger Bar

TRAY-0001
Registration Tray - non electrical,
place holder for non IC new
construction, Ø2.95"